

MATERIAL DESCRIPTION

Coala Pop-Up PET S is a 340 mic white matt polyester compound with grey back. Can be printed with eco-solvent, solvent, latex and UV ink systems.

PRINTER & INK COMPATIBILITY



FILM THICKNESS

340
μ

PRODUCT DESCRIPTION

- Thickness: 340 mic
- Grammage: 415 g/m²
- Gloss 60°: 10 % (ASTM D2457)
- Gloss 85°: 15 % (ASTM D2457)
- Shade (fs): L* 85
a* 0
b* -5

(ANSI T) (D50/2°/Abs/No)

PRINTING & LAMINATING

- Suitable printing condition:
Temperature 15~30°C(59~86°F) / Humidity 30~60%
- Dry Time will vary depending on ink type. It is necessary to dry up and not to overlap the printed material.
- Lamination is optional. In order to protect the image from physical damage, overlamine is recommended.

SHELF LIFE STORAGE AND CONDITIONS



- It is recommended to store in the closed original packing in a cool and dry environment
- Temperature 10°~25°C, Relative Humidity 50% RH
- Processing : within one year after receipt

APPLICATIONS

- Pop-Up displays

BENEFITS

- Good scratch-and water resistance
- Very good stiffness
- Opaque
- Highly dimensionally stable
- Eco-friendly PVC free product

PVC
FREE

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

